UL Product **iQ**™



ZPMV8.E324220 - Wiring, Printed Certified for Canada - Component

Wiring, Printed Certified for Canada - Component

GLOBAL SUCCESS CIRCUITS CO LTD

E324220

Second-Period Of Industrial Park Wan'An County Ji'an, JiangXi 343800 China

Cond Width				Max				Max					
	Min	Min Edge	Cond Thk	SS/	Area Diam	Solder Limits		Assembly Solder Process (IPC)		Oper	Elomo	Meets	
Туре	mm(in)	mm(in)	mic(mil)		mm(in)	°C	sec		Cycles	°C	Class	DSR	i
Multilayer printed wiring boards													
G- 2(Note1)	0.1 (0.004)	0.3 (0.012)	34 (1.34) Int:204	DS	50.8 (2)	288	20	-	-	130	V-0	All	*
W-2	0.075 (0.003)	0.15 (0.006)	17 (0.67) Int:68	DS	50.8 (2)	288	20	-	-	130	V-0	All	*
Single layer metal base printed wiring boards													
AL01	0.22 (0.009)	0.26 (0.01)	34 (1.34)	SS	50.8 (2)	288	20	-	-	90	V-0	All	0
Single layer printed wiring boards													
T-1	0.075 (0.003)	0.15 (0.006)	17 (0.67)	DS	50.8 (2)	288	20	-	-	130	V-0	All	*

^{* -} CTI marking is optional and may be marked on the printed wiring board.

Note1 -& - When the external copper thickness is 34-102mic, the midboard and edge conductor width is 0.10mm and 0.30mm.When the external copper thickness is 102-204mic,the midboard conductor width is 0.40mm,the edge conductor width is 0.42mm.

Marking: Company name or tradename "E324220" or trademark 😂 , 🔃 , type designation and the Recognized Component



. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2021-07-14

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"